

INDUSTRIAL POWER TRANSMISSION SOLUTIONS

Now more than ever it's important to keep things moving

Cone Drive is here to keep you in motion

Having Gearbox Delivery Issues?

Cone Drive offers best in class lead times

Product Features:

- ✓ Industry leading technology
- ✓ High torque, compact design
- ✓ Customized to your application





CONFIGURE & DOWNLOAD YOUR MODEL AT ConeTools.com











Product	Series HP	Series HP-A	Series B	Series RG	Series F
Size	1.50 - 28 in	100 - 200 mm	1.33 - 3.54 in	1.5 - 3.5 in	39 - 76 mm
Construction	Cast Iron	Cast Iron	Aluminum	Cast Iron	316 Stainless Steel
Ratio	5:1 - 343,000:1	5:1 - 70:1	5:1 - 3,600:1	5:1-600:1	5:1 - 600:1
Output Torque (ConstantSpeed)	2,900,000 lb-in	88,100 lb-in	6,370 lb-in	10,800 lb-in	5,950 lb-in
Shock Load Capacity	High	High	Moderate	High	Moderate
IP Rating	N/A	N/A	IP 55	IP 65	IP 69k
Warranty	5 Year	5 Year	2 year	5 year	5 Year

















PRECISION MOTION CONTROL SOLUTIONS

Now more than ever it's important to keep things moving

Cone Drive is here to keep you in motion

Having Gearbox Delivery Issues?

Cone Drive offers best in class lead times

Product Features:

- ✓ Industry leading technology
- ✓ High torque, compact design
- ✓ Customized to your application



0

CONFIGURE & DOWNLOAD YOUR MODEL AT ConeTools.com











Product	Series W	Series HP	Series S	Series RG	Series F
Size	38-89 mm	3.0-8.0 in	1.33-3.54 in	1.5-3.5 in	39-76 mm
Construction	Aluminum	Cast Iron	Aluminum	Cast Iron	316 Stainless Steel
Nominal Backlash	0-24 arcmin	2-35 arcmin	12-41 arcmin	4-27 arcmin	4-27 arcmin
Ratio	5:1-60:1	5:1-70:1	5:1-60:1	5:1-60:1	5:1-60:1
Output Torque (ConstantSpeed)	≤10,800 lb-in	≤ 97,100 lb-in	≤ 6,370 lb-in	≤10,800 lb-in	≤ 5,950 lb-in
Output Torque (Acceleration)	≤ 11,700 lb-in	≤ 121,000 lb-in	≤ 7,540 lb-in	≤ 11,700 lb-in	≤ 6,380 lb-in
IP Rating	IP 65	N/A	IP 55	IP 65	IP 69k
Warranty	5 year	5 Year	2 year	5 year	5 Year













