

Series F Stainless Steel

The Series F Stainless Steel gearbox provides you Cone Drive's gearing technology in a stainless steel package. The smooth contours of the housing allow fluids to wick away preventing bacteria from forming on the surface. When your application demands strict hygenic performance, look no further than Cone Drive's stainless steel Series F gearbox.

FOOD & BEVERAGE | PACKAGING | PHARMACEUTICAL | MEAT & DAIRY | MIXERS



HYGENIC POWER

- Double-enveloping worm gearing supported with two input bearings
- · 316 stainless steel adapter and housing
- Adheres to strict NSF and A3 hygenic standards and carries an ingress protection rating of IP69k
- High efficiency double reduction in single right angle configuration
- Optional torque arm, flange, or side mounting available
- Low or standard backlash
- · Best in class lead times
- 5 year warranty







CONFIGURE & DOWNLOAD YOUR MODEL AT www.ConeTools.com

SERIES F

SPECIFICATIONS

Center Distance: 39 thru 76 mm

Ratio: 5:1 thru 600:1

Reductions: Single or double

Output Torque_{ConstantSpeed}: ≤ 5,950 lb-in

Motor Connection: Non-fretting bushing

Input Shaft: Single or double extended

Output Shaft: Inch or metric, solid (single or

double extended), hollow, shrink disc

Lubricant: Factory filled with food grade

lubricant

I.P. Rating: IP 69K











