C Cone Drive

Series RG

The Series RG gearbox is an adaptable solution for mid range power applications. Available with single or double reduction, the Series RG is designed with Cone Drive's double-enveloping worm gear technology and offers multiple output options. Tapered roller output bearings provide the capacity required to handle heavy overhung loads.

PACKAGING | PLASTICS & RUBBER | STEEL | CONVEYOR | PULP & PAPER

RUGGED PERFORMER

- Double-enveloping worm gearing supported with two input bearings
- Cast iron construction
- High efficiency double reduction in single right angle configuration
- Low or standard backlash
- White epoxy or stainless steel paint available
- Best in class lead times
- 5 year warranty

CONFIGURE & DOWNLOAD YOUR MODEL AT www.ConeTools.com



AIIO

Center Distance: 1.5 thru 3.5 in

Ratio: 5:1 thru 600:1

Reductions: Single or double

Output Torque_{ConstantSpeed}: ≤10,800 lb-in

Motor Connection: Integrated spider coupling (single reduction), Non-fretting bushing (double reduction)

Input Shaft: Single or double extended

Output Shaft: Inch or metric, solid (single or double extended), hollow, shrink disc, mounting flange

Lubricant: Factory filled with synthetic lubricant

I.P. Rating: IP 65

- Cone Drive Operations, Inc.
 240 East 12th Street
 Traverse City, MI 49684, USA
- *****1.888.994.2663
 - orders@conedrive.com
- 📮 conedrive.com





