



Series RG

The Series RG gearbox is an adaptable solution for mid range power applications. Available with single or double reduction, the Series RG is designed with Cone Drive's double-enveloping worm gear technology and offers multiple output options. Tapered roller output bearings provide the capacity required to handle heavy overhung loads.

PACKAGING | PLASTICS & RUBBER | STEEL | CONVEYOR | PULP & PAPER



RUGGED PERFORMER

- Double-enveloping worm gearing supported with two input bearings
- Cast iron construction
- High efficiency double reduction in single right angle configuration
- Low or standard backlash
- White epoxy or stainless steel paint available
- Best in class lead times
- 5 year warranty



CONFIGURE & DOWNLOAD YOUR MODEL AT www.ConeTools.com

SERIES RG

S P E C I F I C A T I O N S

Center Distance: 1.5 thru 3.5 in

Ratio: 5:1 thru 600:1

Reductions: Single or double

Output Torque_{ConstantSpeed} : ≤ 10,800 lb-in

Motor Connection: Integrated spider coupling (single reduction), Non-fretting bushing (double reduction)

Input Shaft: Single or double extended

Output Shaft: Inch or metric, solid (single or double extended), hollow, shrink disc, mounting flange

Lubricant: Factory filled with synthetic lubricant

I.P. Rating: IP 65



Cone Drive Operations, Inc.
240 East 12th Street
Traverse City, MI 49684, USA

+1.888.994.2663
 orders@conedrive.com
 conedrive.com

