

The Series W is Cone Drive's highest precision right angle solution. The Series W has a compact, annodized aluminum housing. The design offers high torsional rigidity and is capable of speeds of up to 6,000 rpm. Quiet and smooth running, the Series W features Cone Drive's double enveloping worm gear technology with optional zero backlash.

PACKAGING | FOOD & BEVERAGE | SATELLITE COMMUNICATION | AUTOMATION & ROBOTICS



## **ULTIMATE PRECISION**

- Double-enveloping worm gearing supported with two input bearings
- Aluminum housing
- Zero, low, or standard backlash
- Angular contact ball bearings (worm shaft)
- Zero backlash bellows style coupling
- Best in class lead times
- 5 year warranty



CONFIGURE & DOWNLOAD YOUR MODEL AT www.ConeTools.com

**SERIES W** 

Center Distance: 38 thru 89 mm

Ratio: 5:1 thru 60:1

Nominal Backlash: 0 - 24 arcmin

Output Torque<sub>ConstantSpeed</sub>: ≤ 10,800 lb-in

Output Torque<sub>Acceleration</sub>: ≤ 11,700 lb-in

Input Shaft: Single or double extended

Output Shaft: Solid (single or double

extended), Hollow, Shrink Disc

**Lubricant:** Factory filled with synthetic

**lubricant** 

I.P. Rating: IP 65



Cone Drive Operations, Inc. 240 East 12th Street Traverse City, MI 49684, USA



+1.888.994.2663





